

## Zero Track Surface Profile. Feed intermediate connector

New

### ■ 06.2541.14 - Black

Feed intermediate connector. Upper feeding cable entry.



### Main specifications

Mountings	Surface
Environment	Indoor dry location

### Electrical


Voltage (V)	24
Emergency	Without
Insulation class	III

### Physical

Color	Black
Weight (kg)	0.01
Length (mm)	82

### Note

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.



Zero Track Surface Profile. Feed intermediate connector



Remote Power Supply Non Dimmable  
24V. 120W. 220/240V  
60.9516



LED power supply source for remote  
installation in 24V/200W electric  
control panel. To avoid problems of  
overload it is recommended to install a  
power source every 185W. 100/240V.  
60.9352



24V Remote power supply. Dimmable  
through 1/10V protocol or Non  
Dimmable. 25W 110/240V  
60.9359



24V Remote power supply. Dimmable  
through 1/10V protocol or Non  
Dimmable. Dimming range 20-100%.  
36W-110V / 45W-240V  
60.9360



24V Remote power supply. Dimmable  
through 1/10V protocol or Non  
Dimmable. 57W 220/240V  
60.9361



24V Remote power supply. Dimmable  
through 1/10V protocol. 120W 110/240V  
60.9416



24V Remote power supply. Dimmable  
through 1/10V protocol. 120W 110/240V  
60.9416

60.9392

60.9426