


Zero Track Surface Profile. Feed intermediate connector

New

06.2541.CZ - Bronze

Feed intermediate connector. Upper feeding cable entry.



Main specifications

Mountings	Surface
Environment	Indoor dry location

Electrical


Voltage (V)	24
Emergency	Without
Insulation class	III

Physical

Color	Bronze
Weight (kg)	0.01
Length (mm)	82

Note


PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.



Zero Track Surface Profile. Feed intermediate connector



Remote Power Supply Non Dimmable
24V. 120W. 220/240V
60.9516



Casambi Controller 220-240V. Remote
Installation
60.9392



LED power supply source for remote
installation in 24V/200W electric
control panel. To avoid problems of
overload it is recommended to install a
power source every 185W. 100/240V.
60.9352



24V Remote power supply. Dimmable
through 1/10V protocol or Non
Dimmable. 25W 110/240V
60.9359



24V Remote power supply. Dimmable
through 1/10V protocol or Non
Dimmable. Dimming range 20-100%.
36W-110V / 45W-240V
60.9360



24V Remote power supply. Dimmable
through 1/10V protocol or Non
Dimmable. 57W 220/240V
60.9361



60.9426

60.9416