

Zero Track Surface Profile. Feed Unit for Remote Power Supply Unit

New

06.2540.18 - Deep Brown

Feed unit for remote power supply unit. Power cable inserting is possible both from the top and the side.



Main specifications

Mountings	Surface
Environment	Indoor dry location

Electrical


Voltage (V)	24.00
Emergency	Without
Insulation class	III

Physical

Color	Deep Brown
Weight (kg)	0.01
Length (mm)	82

Note

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.



Zero Track Surface Profile. Feed Unit for Remote Power Supply Unit



LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V. 60.9352



Remote Power Supply Non Dimmable 24V. 120W. 220/240V 60.9516



24V Remote power supply. Dimmable through DALI protocol. 120W 110/240V 60.9426




24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V 60.9359



24V Remote power supply. Dimmable through 1/10V protocol. 120W 110/240V 60.9416



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. Dimming range 20-100%. 36W-110V / 45W-240V 60.9360



60.9392

Dimmable. 57W 220/240V
60.9361