

Zero Track Surface Profile. Interior ceiling/ceiling-wall/wall curve

■ 06.2544.18 - Deep Brown

Interior ceiling/ceiling-wall/wall curve. Can be powered via connections on the back.

Interior ceiling/ceiling-wall/wall curve. Can be powered via connections on the back.



Main specifications


Mountings	Surface
Environment	Indoor

Electrical

Voltage (V)	24.00
Driver	Remote
Emergency	Without
Insulation class	III

Physical

Color	Deep Brown
Weight (kg)	0.01
Length (mm)	82



Certification / Marking



Zero Track Surface Profile. Interior ceiling/ceiling-wall/wall curve



Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. Dimming range 20-100%. 36W-110V / 45W-240V
60.9360

Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V
60.9359

Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V
60.9361



Remote power supply. Dimmable through 1/10V protocol. 120W 110/240V
60.9416

Remote power supply. Dimmable through DALI protocol. 120W 110/240V
60.9426

Casambi Broadcast. Remote Installation
60.9392



LED power supply source for remote installation in 24V/200W electric control panel
60.9358

