

## Zero Track Surface Profile. T-shaped connector

New

■ **06.2545.18 - Deep Brown**

T-shaped connector. Can be powered via connections on the back.



### Main specifications

<b>Mountings</b>	Surface
<b>Environment</b>	Indoor dry location

### Electrical


<b>Voltage (V)</b>	24.00
<b>Emergency</b>	Without
<b>Insulation class</b>	III

### Physical

<b>Color</b>	Deep Brown
<b>Weight (kg)</b>	0.01
<b>Length (mm)</b>	75

### Note

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.



## Zero Track Surface Profile. T-shaped connector



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V  
60.9361

24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. Dimming range 20-100%. 36W-110V / 45W-240V  
60.9360

Casambi Controller 220-240V. Remote Installation  
60.9392



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V  
60.9359

LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.  
60.9352

24V Remote power supply. Dimmable through DALI protocol. 120W 110/240V  
60.9426



60.9516

60.9416