


Zero Track Surface Profile. T-shaped connector

New

06.2545.40 - White

T-shaped connector. Can be powered via connections on the back.



Main specifications

Mountings	Surface
Environment	Indoor dry location

Electrical


Voltage (V)	24.00
Emergency	Without
Insulation class	III

Physical

Color	White
Weight (kg)	0.01
Length (mm)	75

Note

PWM voltage output dimmable drivers shall be used at frequencies between 250 and 500Hz.



Zero Track Surface Profile. T-shaped connector



LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V. 60.9352



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 25W 110/240V 60.9359



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. Dimming range 20-100%. 36W-110V / 45W-240V 60.9360



24V Remote power supply. Dimmable through 1/10V protocol or Non Dimmable. 57W 220/240V 60.9361



24V Remote power supply. Dimmable through DALI protocol. 120W 110/240V 60.9426



24V Remote power supply. Dimmable through 1/10V protocol. 120W 110/240V 60.9416



Remote Power Supply Non Dimmable



Casambi Controller 220-240V. Remote

