

C1 Mono Spot Ceiling Small Ø 35

■ 03.1221.DR - Anthrazit




Verstellbare LED-Leuchte für den Innenbereich, geeignet für Deckenmontagen. Das Gehäuse kann aus der Installationsfläche herausgezogen werden, so dass eine Ausrichtung von 60° vertikal und 355° horizontal möglich ist. Integrierte Full-Cut-Off optische Gruppe. Die Fernspeisung (nicht enthalten) muss an einer zugänglichen Stelle angebracht werden.

Verstellbare LED-Leuchte für den Innenbereich, geeignet für Deckenmontagen. Das Gehäuse kann aus der Installationsfläche herausgezogen werden, so dass eine Ausrichtung von 60° vertikal und 355° horizontal möglich ist.

Integrierte Full-Cut-Off optische Gruppe.

Die Fernspeisung (nicht enthalten) muss an einer zugänglichen Stelle angebracht werden.




Hauptspezifikationen

Leuchtenkategorie	LED	Halterungen	Decke
Leistung (W)	6W	Umgebung	Innenbeleuchtung
CCT (K)	2700K		
CRI	90		
Nettolumen (lm)	368		

Optisch

Beleuchtungstyp	Direkt
LED-Typ	Leistungs-LED
Light distribution	Symmetrisch
Optiktyp	Medium
Strahlungswinkel (°)	18
Beam angle C90-270 (°)	18



Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2640	0.32
2	660	0.65
3	293	0.97
4	165	1.30
5	106	1.62


Luminous flux luminaire
368 lm

Elektrisch

Strom (mA)	500
Dimmbar	Yes
Treiber	remote
	Ausgeschlossen
Notfall	Ohne
Isolationsklasse	III

Physikalisch

Farbe	Anthrazit	Lichtfleckdurchmesser 35
Ausrichtung	einstellbar	(mm)
Gewicht (kg)	0.18	
Neigung (°)	60	
Drehung (°)	355	



C1 Mono Spot Ceiling Small Ø 35



Coated aluminum mount for surface
installation (ceiling)
08.0211.ES



Non dimmable continuous current
power supply. 15-30W, 220/240V
-50/60Hz with power current selected
through adjustable switch. 350mA –
15W / 400mA – 17W / 450mA – 19W /
500mA – 22W / 550mA – 24W / 600mA –
26W / 650mA – 28W / 700mA – 30W no
regulable
60.9592



Continuous current supply source 240V
– 50/60Hz with dimmable DALI 2, push
dimming. 300mA-16W / 350mA-18W /
400mA-21W / 500mA-27W / 600mA-32W
/ 650mA-35W
700/750/800/900/950/1000/1050mA-38W
60.9186



Continuous current power supply,
dimmable Casambi 220/240V-50/60Hz,
300mA-16W / 350mA-18,5W / 400mA-
21,5W / 450mA-24W / 500mA-27W /
600mA-32W / 650mA-35W / 700mA-36W
/ 750/800/900/1000/1050mA – 38W
60.9207



Coated aluminum mount for surface
installation (ceiling)
08.0211.DY



Coated aluminum mount for surface
installation (ceiling)
08.0211.DR



Coated aluminum mount for surface
installation (ceiling)
08.0211.EQ



Coated aluminum mount for surface
installation (ceiling)
08.0211.ER



ø82

No Trim installation frame for ceiling
mounting
08.0208.00