


Johnny 120 Semi-Recessed 1L Square – Housing

08.0506.40 - Weiss

LED Einbauleuchte. Ohne Netzgerät. Es wird ein Gerät als Lichtquelle benötigt.



Hauptspezifikationen



Halterungen	Decke, eingebaut
Umgebung	Innenbeleuchtung

Elektrisch

Notfall	Ohne
Isolationsklasse	III

Physikalisch

Farbe	Weiss
Gewicht (kg)	0.30



Johnny 120 Semi-Recessed 1L Square – Housing



Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable 250 mA – 10W / 350 mA – 15W / 400 mA – 17W / 450 mA – 19W / 500/550/600/700 mA – 20W, Dali 1 switch.
60.8847

Continuous current power supply 220/240V – 50/60Hz. Adjustable Current 300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-42W
60.9162

Snoot shielding cone
08.0526.40



Flood lens
08.8432.00

Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming
60.9188


Snoot shielding cone
08.0526.BW



Continuous current power supply.
230/240V – 50/60Hz. Adjustable Current
350mA – 17W / 500mA – 24W / 700/ 750
mA – 32W switch by trailing and
leading edge dimming, mains dimming
or push dimming
60.8534

Honeycomb
08.8428.00

Snout shielding cone
08.0526.00



Continuous current power supply of
18W, 220/240V – 50/60Hz with 450 mA
supply voltage Mains dimming, trailing
edge
60.9268

Elliptical lens
08.8431.00