

Johnny 120 Square 2L – Recessed Universal Frame

■ 08.0501.00 - Schwarz

LED Einbauleuchte. Ohne Netzgerät. Es wird ein Gerät als Lichtquelle benötigt.

Hauptspezifikationen

Halterungen	Decke, eingebaut
Umgebung	Innenbeleuchtung

Elektrisch


Notfall	Ohne
Isolationsklasse	III

Physikalisch

Farbe	Schwarz
Gewicht (kg)	0.30

Note

Einmalige Referenz für Trim- oder No-Trim-Deckeneinbau. 08.0551.00=enthält weißer Rahmen, um den Trim-Einbau zu vervollständigen. 08.0501.00=enthält, optional, weißer und schwarzer Rahmen, um den Trim-Einbau zu vervollständigen.



Johnny 120 Square 2L – Recessed Universal Frame



Continuous current power supply of 10-20W, 110/240V – 50/60Hz with power current selected through adjustable 250 mA – 10W / 350 mA – 15W / 400 mA – 17W / 450 mA – 19W / 500/550/600/700 mA – 20W, Dali 1 switch.
60.8847

Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming
60.9188

Flood lens
08.8432.00



Honeycomb
08.8428.00

Snoot shielding cone
08.0526.BW

Snoot shielding cone
08.0526.40



Continuous current power supply.


Continuous current power supply of

Continuous current power supply

mA – 32W switch by trailing and
leading edge dimming, mains dimming
or push dimming
60.8534

edge
60.9268

/ 450mA-20W / 500mA-22W / 550mA-
24W / 600mA-27W / 650mA-29W /
700mA-31W / 750mA-32W / 800mA-33W
/ 850mA-35W / 900mA-38W / 950mA-
40W / 1000/1050mA-42W
60.9162



Snoot shielding cone
08.0526.00

Elliptical lens
08.8431.00