

Johnny 120 Square 2L – Recessed Universal Frame

08.0551.00 - Weiss

LED Einbauleuchte. Ohne Netzgerät. Es wird ein Gerät als Lichtquelle benötigt.

Hauptspezifikationen

Halterungen	Decke, eingebaut
Umgebung	Innenbeleuchtung

Elektrisch















































































Notfall	Ohne
Isolationsklasse	III

Physikalisch

Farbe	Weiss
Gewicht (kg)	0.30

Note

Einmalige Referenz für Trim- oder No-Trim-Deckeneinbau. 08.0551.00=enthält weißer Rahmen, um den Trim-Einbau zu vervollständigen. 08.0501.00=enthält, optional, weißer und schwarzer Rahmen, um den Trim-Einbau zu vervollständigen.



Johnny 120 Square 2L – Recessed Universal Frame



Snoot shielding cone
08.0526.40



Snoot shielding cone
08.0526.00



Elliptical lens
08.8431.00



Continuous current power supply of
18W, 220/240V – 50/60Hz with 450 mA
supply voltage Mains dimming, trailing
edge
60.9268



Continuous current power supply.
230/240V – 50/60Hz. Adjustable Current
350mA – 17W / 500mA – 24W / 700/ 750
mA – 32W switch by trailing and
leading edge dimming, mains dimming
or push dimming
60.8534



Continuous current power supply
220/240V – 50/60Hz. Adjustable Current
300mA-13W / 350mA-15W / 400mA-18W
/ 450mA-20W / 500mA-22W / 550mA-
24W / 600mA-27W / 650mA-29W /
700mA-31W / 750mA-32W / 800mA-33W
/ 850mA-35W / 900mA-38W / 950mA-
40W / 1000/1050mA-42W
60.9162



current selected through adjustable
250 mA – 10W / 350 mA – 15W / 400 mA
– 17W / 450 mA – 19W / 500/550/600/700
mA – 20W, Dali 1 switch.
60.8847



Snoot shielding cone
08.0526.BW

Continuous current power supply of
13-20W, 110/240V – 50/60Hz with power
current selected through adjustable
300 mA – 15W / 350 mA – 18W /
400/450/500/550/600/
650/700/750/800/850/900 mA – 15W.
switch. 0/1-10V or push dimming
60.9188