

 03.8930.40ADA - Weiß/Chrom


Anzahl an Köpfen	1	Nettolumen (lm)	805
Leuchtenkategorie	LED	Halterungen	Decke, eingebaut
Leistung (W)	10.8W	Umgebung	Innenbeleuchtung
CCT (K)	3000K		
CRI	90		

Technical drawing of a 4-hole plate. The drawing includes three views: a top view showing a rectangular plate with dimensions 75x163 and a thickness of 12,5; a front view showing a width of 60 and a distance of 149 between the centers of the four holes; and a side view showing a height of 55. The holes are arranged in a 2x2 grid.

Frequenz (Hz)	50/60	Notfall	Ohne
Spannung (V)	220.00	Isolationsklasse	II
Dimmbar	Yes		
Treiber	remote		
	Enthalten		
Treiber-Typ	Elektronisch		
	dimmbar DALI		

Farbe	Weiß/Chrom	Länge (mm)	149
Ausrichtung	einstellbar		
Einbautiefe (mm)	75		
Gewicht (kg)	0.34		
Neigung (°)	30		

Vorinstallationsrahmen. Muss separat bestellt werden.



Light Shadow Adjustable No Trim Dali Version 4 Spots Optic Spot



Pre-installation Frame
08.0516.00

Accessory for mounting of No Trim
continuous line.
08.0059.90