


Light Shadow Pro Ø 60 Fixed Optic Medium

Neues Produkt

03.9951.40 - Weiss

LED-Beleuchtungsmodul mit geringer Blendung für die Einsetzung in Einbaurahmen (nicht inbegriffen).
Installation mittels Bajonettsystem mit austauschbaren Spots. Remote-Treiber nicht enthalten.




Hauptspezifikationen

Anzahl an Köpfen	1	Nettolumen (lm)	1180
Leuchtenkategorie	LED	Halterungen	Recessed
Leistung (W)	15W	Umgebung	Innenbeleuchtung
CCT (K)	2700K		
CRI	90		

Optisch

Beleuchtungstyp	Direkt
LED-Typ	LED-Anordnung
Light distribution	Symmetrisch
Optiktyp	Medium
Strahlungswinkel (°)	25
Beam angle C90-270 (°)	25



Beam Angle: 25°

h(m) E(lx) D(m)

1 6735 0.45

2 1684 0.90

3 748 1.36

4 421 1.81

5 269 2.26

Luminous flux luminaire
1180 lm

Elektrisch

Strom (mA)	400	Isolationsklasse	III
Dimmbar	Yes		
Treiber	remote Ausgeschlossen		
Treiber-Typ	nicht dimmbarer , Dimmable DALI 2, Elektronisch dimmbar, Electronic dimmbare CASAMBI, Elektronisch dimmbar 1-10 V, Elektronisch dimmbar DALI, Triac Ohne		

Notfall

Physikalisch

Farbe	Weiss
Ausrichtung	fest
Einbautiefe (mm)	91
Gewicht (kg)	0.22
Lichtfleckdurchmesser (mm)	60

Note

Bitte wählen Sie 300 mA Einstellung im Remote-Treiber, um die Leistung der "Adjustable" Version zu entsprechen.

Light Shadow Pro Ø 60 Fixed Optic Medium



Installation Frame Trim
08.0160.40



Installation Frame Trim
08.0160.14



Continuous current power supply, 0/1-10V dimmable, 220/240V – 50/60Hz, 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W / 700/750/800/900/950/1000/1050mA-36W
60.9439



Continuous current power supply of 13-20W, 110/240V – 50/60Hz with power current selected through adjustable 300 mA – 15W / 350 mA – 18W / 400/450/500/550/600/ 650/700/750/800/850/900 mA – 15W. switch. 0/1-10V or push dimming
60.9188



Continuous current supply source 240V – 50/60Hz with dimmable DALI 2, push dimming. 300mA-16W / 350mA-18W / 400mA-21W / 500mA-27W / 600mA-32W / 650mA-35W 700/750/800/900/950/1000/1050mA-38W
60.9186



Continuous current power supply of 12-20W, 110/240V – 50/60Hz with power current selected through adjustable 350mA – 17W / 400mA – 19W / 450 / 550 / 600 / 700mA – 20W regulable Dali 1 y Dali 2
60.9222



Installation Frame No Trim
08.0192.00



Non dimmable continuous current
power supply of 220/240V – 50/60Hz
with power current selected through
adjustable with switch 200 mA – 8,5W /
300 mA – 13W / 350 mA – 15W / 400 mA
– 17,5W / 450 mA – 19,5W / 500 mA –
22W
60.9160



Continuous current power supply,
Mains dimming, leading & trailing edge
220/240V – 50/60Hz, 300mA-14W /
350mA-17W / 400mA-19W /
450/500/600/650/700/750/800/900mA –
20W
60.9467



Continuous current power supply,
dimmable Casambi 220/240V-50/60Hz,
300mA-16W / 350mA-18,5W / 400mA-
21,5W / 450mA-24W / 500mA-27W /
600mA-32W / 650mA-35W / 700mA-36W
/750/800/900/1000/1050mA – 38W
60.9207