


Light Supply Adjustable No Trim

■ 03.6620.40 - Weiss

LED Einbauleuchte. Fernnetzgerät mit 220/240V im Lieferumfang enthalten.




Hauptspezifikationen

Anzahl an Köpfen	1	Nettolumen (lm)	1725
Leuchtenkategorie	LED	Halterungen	Decke, eingebaut
Leistung (W)	28W	Umgebung	Innenbeleuchtung
CCT (K)	4000K		
CRI	80		

Optisch

Beleuchtungstyp	Direkt
LED-Typ	Phosphor LED
Light distribution	Symmetrisch
Optiktyp	Scheinwerfer
Strahlungswinkel (°)	33
Beam angle C90-270 (°)	33



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	5127	0.60
2	1282	1.19
3	570	1.79
4	320	2.39
5	205	2.99

Luminous flux luminaire
1725 lm (EXTREME CUT OFF)

Elektrisch


Frequenz (Hz)	50/60	Isolationsklasse	II
Dimmbar	No		
Treiber	remote		
	Enthalten		
Treiber-Typ	nicht dimmbarer		
Notfall	Ohne		

Physikalisch

Farbe	Weiss	Drehung (°)	355
Ausrichtung	einstellbar		
Einbautiefe (mm)	239		
Gewicht (kg)	1.01		
Neigung (°)	35		

Note

Vormontagerahmen oder Soft Architecture Montageplatte für No Trim Ausführung. Muss separat bestellt werden.



Light Supply Adjustable No Trim



Light Supply Adjustable spare reflector. Medium
08.8414.00



Light Supply Adjustable spare reflector. Flood
08.8415.00



Honeycomb. Big Cells
08.8377.14



Light Supply Adjustable spare reflector. Spot
08.8413.00



Honeycomb. Small Cells
08.8049.14



Elliptical lens
08.8118.68



Screening crosspiece
08.8242.14



Pre-installation frame
08.8119.00



Soft Architecture installation plate
SA.6600.1