


## Light Supply Adjustable No Trim

03.6819.40A - Weiss

LED Einbauleuchte. Fernnetzgerät mit 220/240V im Lieferumfang enthalten.




### Hauptspezifikationen

Anzahl an Köpfen	1	Nettolumen (lm)	1486
Leuchtenkategorie	LED	Halterungen	Decke, eingebaut
Leistung (W)	30.1W	Umgebung	Innenbeleuchtung
CCT (K)	4000K		
CRI	90		

### Optisch

Beleuchtungstyp	Direkt
LED-Typ	LED-Anordnung
Light distribution	Symmetrisch
Optiktyp	Medium
Strahlungswinkel (°)	21
Beam angle C90-270 (°)	21



Beam Angle:	21°		
	h(m)	E(lx)	D(m)
1	8164	0.37	
2	2041	0.75	
3	907	1.12	
4	510	1.49	
5	327	1.87	

Luminous flux luminaire  
1486 lm (EXTREME CUT OFF)

### Elektrisch


Frequenz (Hz)	50/60	Notfall	Ohne
Spannung (V)	37.60	Isolationsklasse	II
Dimmbar	No		
Treiber	remote		
	Enthalten		
Treiber-Typ	nicht		
	dimmbarer		

### Physikalisch

Farbe	Weiss	Drehung (°)	355
Ausrichtung	einstellbar		
Einbautiefe (mm)	239		
Gewicht (kg)	1.01		
Neigung (°)	35		

### Note

Vormontagerahmen oder Soft Architecture Montageplatte für No Trim Ausführung. Muss separat bestellt werden.



## Light Supply Adjustable No Trim



---

Light Supply Adjustable spare reflector. Medium  
08.8451.00



---

Pre-installation frame  
08.8119.00



---

Honeycomb. Small Cells  
08.8049.14



---

Honeycomb. Big Cells  
08.8377.14



---

Elliptical lens  
08.8118.68



---

Screening crosspiece  
08.8242.14



---

Highly-efficient cylinder  
08.8453.40



---

Light Supply Adjustable spare reflector. Flood  
08.8452.00



---

Light Supply Adjustable spare reflector. Spot  
08.8450.00



---

Soft Architecture installation plate  
SA.6600.1