


Light Supply Adjustable No Trim

03.6821.40A - Weiss

LED Einbauleuchte. Fernnetzgerät mit 220/240V im Lieferumfang enthalten.




Hauptspezifikationen

Anzahl an Köpfen	1	Nettolumen (lm)	1698
Leuchtenkategorie	LED	Halterungen	Decke, eingebaut
Leistung (W)	30.1W	Umgebung	Innenbeleuchtung
CCT (K)	3000K		
CRI	90		

Optisch

Beleuchtungstyp	Direkt
LED-Typ	LED-Anordnung
Light distribution	Symmetrisch
Optiktyp	Strahler
Strahlungswinkel (°)	13
Beam angle C90-270 (°)	13



Luminous flux luminaire
1698 lm (EXTREME CUT OFF)

Elektrisch

Frequenz (Hz)	50/60	Notfall	Ohne
Spannung (V)	37.60	Isolationsklasse	II
Dimmbar	No		
Treiber	remote		
	Enthalten		
Treiber-Typ	nicht		
	dimmbarer		

Physikalisch

Farbe	Weiss	Drehung (°)	355
Ausrichtung	einstellbar		
Einbautiefe (mm)	239		
Gewicht (kg)	1.01		
Neigung (°)	35		

Note

Vormontagerahmen oder Soft Architecture Montageplatte für No Trim Ausführung. Muss separat bestellt werden.



Light Supply Adjustable No Trim



Light Supply Adjustable spare reflector. Medium
08.8451.00



Pre-installation frame
08.8119.00



Honeycomb. Small Cells
08.8049.14



Honeycomb. Big Cells
08.8377.14



Elliptical lens
08.8118.68



Screening crosspiece
08.8242.14



Highly-efficient cylinder
08.8453.40



Light Supply Adjustable spare reflector. Flood
08.8452.00



Light Supply Adjustable spare reflector. Spot
08.8450.00



Soft Architecture installation plate
SA.6600.1