

Light Supply Adjustable No Trim

03.6823.40A - Weiss

LED Einbauleuchte. Fernnetzgerät mit 220/240V im Lieferumfang enthalten.




Hauptspezifikationen

Anzahl an Köpfen	1	Nettolumen (lm)	1508
Leuchtenkategorie	LED	Halterungen	Decke, eingebaut
Leistung (W)	30.1W	Umgebung	Innenbeleuchtung
CCT (K)	3000K		
CRI	90		

Optisch

Beleuchtungstyp	Direkt
LED-Typ	LED-Anordnung
Light distribution	Symmetrisch
Optiktyp	Scheinwerfer
Strahlungswinkel (°)	39
Beam angle C90-270 (°)	39



Beam Angle: 39°

h(m)	E(lx)	D(m)
1	4225	0.71
2	1056	1.42
3	469	2.14
4	264	2.85
5	169	3.56

Luminous flux luminaire
1508 lm (EXTREME CUT OFF)

Elektrisch


Frequenz (Hz)	50/60	Notfall	Ohne
Spannung (V)	37.60	Isolationsklasse	II
Dimmbar	No		
Treiber	remote		
	Enthalten		
Treiber-Typ	nicht		
	dimmbarer		

Physikalisch

Farbe	Weiss	Drehung (°)	355
Ausrichtung	einstellbar		
Einbautiefe (mm)	239		
Gewicht (kg)	1.01		
Neigung (°)	35		

Note

Vormontagerahmen oder Soft Architecture Montageplatte für No Trim Ausführung. Muss separat bestellt werden.



Light Supply Adjustable No Trim



Light Supply Adjustable spare reflector. Medium
08.8451.00

Pre-installation frame
08.8119.00

Honeycomb. Small Cells
08.8049.14



Honeycomb. Big Cells
08.8377.14

Elliptical lens
08.8118.68

Screening crosspiece
08.8242.14



Highly-efficient cylinder
08.8453.40

Light Supply Adjustable spare reflector. Flood
08.8452.00

Light Supply Adjustable spare reflector. Spot
08.8450.00



Soft Architecture installation plate
SA.6600.1