

Light Supply Adjustable No Trim Dimmable

03.6819.40ADA - Weiss

LED Einbauleuchte. Fernnetzgerät mit 220/240V im Lieferumfang enthalten.




Hauptspezifikationen

Anzahl an Köpfen	1	Nettolumen (lm)	1486
Leuchtenkategorie	LED	Halterungen	Decke, eingebaut
Leistung (W)	30.1W	Umgebung	Innenbeleuchtung
CCT (K)	4000K		
CRI	90		

Optisch

Beleuchtungstyp	Direkt
LED-Typ	LED-Anordnung
Light distribution	Symmetrisch
Optiktyp	Medium
Strahlungswinkel (°)	21
Beam angle C90-270 (°)	21



Beam Angle: 21°

h(m)	E(lx)	D(m)
1	8164	0.37
2	2041	0.75
3	907	1.12
4	510	1.49
5	327	1.87

Luminous flux luminaire
1486 lm (EXTREME CUT OFF)

Elektrisch


Frequenz (Hz)	50/60	Notfall	Ohne
Spannung (V)	37.60	Isolationsklasse	II
Dimmbar	Yes		
Treiber	remote		
	Enthalten		
Treiber-Typ	Elektronisch		
	dimmbare 1-10 V,		
	Elektronisch		
	dimmbare DALI		

Physikalisch

Farbe	Weiss	Drehung (°)	355
Ausrichtung	einstellbar		
Einbautiefe (mm)	239		
Gewicht (kg)	1.01		
Neigung (°)	35		

Note

Vormontagerahmen oder Soft Architecture Montageplatte für No Trim Ausführung. Muss separat bestellt werden.



Light Supply Adjustable No Trim Dimmable



Light Supply Adjustable spare reflector. Medium
08.8451.00

Pre-installation frame
08.8119.00

Honeycomb. Big Cells
08.8377.14



Highly-efficient cylinder
08.8453.40

Soft Architecture installation plate
SA.6600.1

Honeycomb. Small Cells
08.8049.14



Elliptical lens
08.8118.68

Screening crosspiece
08.8242.14

Light Supply Adjustable spare reflector. Flood
08.8452.00



Light Supply Adjustable spare
reflector. Spot
08.8450.00