

## Light Supply Adjustable No Trim Dimmable

03.6823.40ADA - Weiss

LED Einbauleuchte. Fernnetzgerät mit 220/240V im Lieferumfang enthalten.




### Hauptspezifikationen

|                   |       |                 |                  |
|-------------------|-------|-----------------|------------------|
| Anzahl an Köpfen  | 1     | Nettolumen (lm) | 1508             |
| Leuchtenkategorie | LED   | Halterungen     | Decke, eingebaut |
| Leistung (W)      | 30.1W | Umgebung        | Innenbeleuchtung |
| CCT (K)           | 3000K |                 |                  |
| CRI               | 90    |                 |                  |

### Optisch

|                        |               |
|------------------------|---------------|
| Beleuchtungstyp        | Direkt        |
| LED-Typ                | LED-Anordnung |
| Light distribution     | Symmetrisch   |
| Optiktyp               | Scheinwerfer  |
| Strahlungswinkel (°)   | 39            |
| Beam angle C90-270 (°) | 39            |



|             |       |      |
|-------------|-------|------|
| Beam Angle: |       | 39°  |
| h(m)        | E(lx) | D(m) |
| 1           | 4225  | 0.71 |
| 2           | 1056  | 1.42 |
| 3           | 469   | 2.14 |
| 4           | 264   | 2.85 |
| 5           | 169   | 3.56 |

Luminous flux luminaire  
1508 lm (EXTREME CUT OFF)

### Elektrisch


|               |                  |                  |      |
|---------------|------------------|------------------|------|
| Frequenz (Hz) | 50/60            | Notfall          | Ohne |
| Spannung (V)  | 37.60            | Isolationsklasse | II   |
| Dimmbar       | Yes              |                  |      |
| Treiber       | remote           |                  |      |
|               | Enthalten        |                  |      |
| Treiber-Typ   | Elektronisch     |                  |      |
|               | dimmbare 1-10 V, |                  |      |
|               | Elektronisch     |                  |      |
|               | dimmbare DALI    |                  |      |

### Physikalisch

|                  |             |             |     |
|------------------|-------------|-------------|-----|
| Farbe            | Weiss       | Drehung (°) | 355 |
| Ausrichtung      | einstellbar |             |     |
| Einbautiefe (mm) | 239         |             |     |
| Gewicht (kg)     | 1.01        |             |     |
| Neigung (°)      | 35          |             |     |

### Note

Vormontagerahmen oder Soft Architecture Montageplatte für No Trim Ausführung. Muss separat bestellt werden.



Light Supply Adjustable No Trim Dimmable



Light Supply Adjustable spare reflector. Medium  
08.8451.00

Pre-installation frame  
08.8119.00

Honeycomb. Big Cells  
08.8377.14



Highly-efficient cylinder  
08.8453.40

Soft Architecture installation plate  
SA.6600.1

Honeycomb. Small Cells  
08.8049.14



Elliptical lens  
08.8118.68

Screening crosspiece  
08.8242.14

Light Supply Adjustable spare reflector. Flood  
08.8452.00



---

Light Supply Adjustable spare  
reflector. Spot  
08.8450.00