


03.9502.40 - Weiss

## Hauptspezifikationen

|                    |       |                 |                  |
|--------------------|-------|-----------------|------------------|
| Anzahl an Köpfen   | 1     | CRI             | 90               |
| Leuchtenkategorie  | LED   | Nettolumen (lm) | 4914             |
| Leistung (W)       | 58W   | Halterungen     | Aufhängung       |
| Systemleistung (W) | 60    | Umgebung        | Innenbeleuchtung |
| CCT (K)            | 3000K |                 |                  |

|                        |                  |
|------------------------|------------------|
| Beleuchtungstyp        | Indirekt, Direkt |
| LED-Typ                | Top LED          |
| Light distribution     | Symmetrisch      |
| Optiktyp               | Streulicht       |
| Strahlungswinkel (°)   | 100              |
| Beam angle C90-270 (°) | 101              |
| UGRL                   | 19               |
| Effizienz (lm/W)       | 81.9             |



Beam Angle DIR: 100°

| h(m) | E(lx) | D(m)  |
|------|-------|-------|
| 1    | 1229  | 2.39  |
| 2    | 307   | 4.78  |
| 3    | 137   | 7.17  |
| 4    | 77    | 9.57  |
| 5    | 49    | 11.96 |

Luminous flux lumineuse  
4914 lm


|              |                                                      |
|--------------|------------------------------------------------------|
| Spannung (V) | 55.80                                                |
| Strom (mA)   | 1050                                                 |
| Dimmbar      | Yes                                                  |
| Treiber      | Remote                                               |
| Treiber-Typ  | nicht<br>dimmbarer ,<br>Elektronisch<br>dimmbar DALI |

|                  |      |
|------------------|------|
| Notfall          | Ohne |
| Isolationsklasse | III  |


|                       |        |
|-----------------------|--------|
| Farbe                 | Weiss  |
| Ausrichtung           | fest   |
| Gewicht (kg)          | 1.45   |
| Länge (mm)            | 1500   |
| Lebensdauer (L70 B10) | L80B50 |

Kabel 4,25 m

Super Line Up&Down Indirect




Recessed Kit 60W. Dali Version  
08.0523.40




Recessed Kit 60W. Non Dimmable  
08.0522.14




Remote Power Supply Kit 60W. Non Dimmable  
08.0524.02




Surface Kit 60W. Non Dimmable  
08.0520.40




Recessed Kit 60W. Non Dimmable  
08.0522.40




Recessed Kit 60W. Dali Version  
08.0523.14



Recessed Kit 60W. Dali Version  
08.0523.02



Surface Kit 60W. Dali Version  
08.0521.14




Recessed Kit 60W. Non Dimmable  
08.0522.02




Remote Power Supply Kit 60W. Non Dimmable  
08.0524.40




Remote Power Supply Kit 60W. Non Dimmable  
08.0524.14



Surface Kit 60W. Dali Version  
08.0521.40



Surface Kit 60W. Non Dimmable  
08.0520.14




Surface Kit 60W. Non Dimmable  
08.0520.02



Remote Power Supply Kit 60W. Dali Version  
08.0525.40



Remote Power Supply Kit 60W. Dali Version  
08.0525.02



Surface Kit 60W. Dali Version  
08.0521.02



Remote Power Supply Kit 60W. Dali Version  
08.0525.14