


## Suspension Cone Ø 300

Neues Produkt

### ■ 03.8440.14 - Schwarz

Pendelleuchte mit integriertem Befestigungssystem für die Installation in Infra-Structure Episode 2. Jedes Leuchtelement wird mit einem 4 meter langen Stromkabel mit einer Mikro-Ausgangsbuchse vervollständigt.

Pendelleuchte mit integriertem Befestigungssystem für die Installation in Infra-Structure Episode 2. Jedes Leuchtelement wird mit einem 4 meter langen Stromkabel mit einer Mikro-Ausgangsbuchse vervollständigt.




### Hauptspezifikationen

Anzahl an Köpfen	1	Nettolumen (lm)	1134
Leuchtenkategorie	LED	Halterungen	Decke
Leistung (W)	30W	Umgebung	Innenbeleuchtung
CCT (K)	2700K		
CRI	90		

### Optisch

Beleuchtungstyp	Direkt
LED-Typ	Top LED
Light distribution	Symmetrisch
Strahlungswinkel (°)	62
Beam angle C90-270 (°)	62



Beam Angle:	62°		
	h(m)	E(lx)	D(m)
1	1200	1.20	
2	300	2.40	
3	133	3.59	
4	75	4.79	
5	48	5.99	

Luminous flux luminaire  
1134 lm

### Elektrisch

Dimmbar	Yes
Treiber	remote Ausgeschlossen
Notfall	Ohne
Isolationsklasse	III

### Physikalisch

Farbe	Schwarz
Ausrichtung	fest
Lichtfleckdurchmesser (mm)	300



# Suspension Cone Ø 300



DALI 12-48V Dimmer  
60.9678



LED Power Supply Source for remote installation. 48V. 100Vac (150W)-240Vac (200W)  
60.9607



Casambi Controller 220-240V. Remote Installation  
60.9392



0/1-10V & Push 12-48V Dimmer  
60.9395



LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac  
60.8919



LED power supply source for remote installation, 48V/120W. 220/240 Vac  
60.9170