


Suspension Cone Ø 300

Neues Produkt

03.8442.40 - Weiss



Pendelleuchte mit integriertem Befestigungssystem für die Installation in Infra-Structure Episode 2. Jedes Leuchtelement wird mit einem 4 meter langen Stromkabel mit einer Mikro-Ausgangsbuchse vervollständigt.


Pendelleuchte mit integriertem Befestigungssystem für die Installation in Infra-Structure Episode 2. Jedes Leuchtelement wird mit einem 4 meter langen Stromkabel mit einer Mikro-Ausgangsbuchse vervollständigt.

Hauptspezifikationen

Anzahl an Köpfen	1	Nettolumen (lm)	1883
Leuchtenkategorie	LED	Halterungen	Decke
Leistung (W)	30W	Umgebung	Innenbeleuchtung
CCT (K)	3000K		
CRI	90		

Optisch

Beleuchtungstyp	Direkt
LED-Typ	Top LED
Light distribution	Symmetrisch
Strahlungswinkel (°)	65
Beam angle C90-270 (°)	65



Beam Angle:	65°		
	h(m)	E(lx)	D(m)
1	1509	1.27	
2	377	2.53	
3	168	3.80	
4	94	5.06	
5	60	6.33	

Luminous flux luminaire
1883 lm

Elektrisch

Dimmbar	Yes
Treiber	remote Ausgeschlossen
Notfall	Ohne
Isolationsklasse	III

Physikalisch

Farbe	Weiss
Ausrichtung	fest
Lichtfleckdurchmesser (mm)	300



Suspension Cone Ø 300



DALI 12-48V Dimmer
60.9678



LED Power Supply Source for remote installation. 48V. 100Wac (150W)-240Vac (200W)
60.9607



Casambi Controller 220-240V. Remote Installation
60.9392



0/1-10V & Push 12-48V Dimmer
60.9395



LED power supply source for remote installation, 48V/120W. 220/240 Vac
60.9170



LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac
60.8919