

Suspension Cone Ø 400

Neues Produkt

■ 03.8441.14 - Schwarz

Pendelleuchte mit integriertem Befestigungssystem für die Installation in Infra-Structure Episode 2. Jedes Leuchtelement wird mit einem 4 meter langen Stromkabel mit einer Mikro-Ausgangsbuchse vervollständigt.


Pendelleuchte mit integriertem Befestigungssystem für die Installation in Infra-Structure Episode 2. Jedes Leuchtelement wird mit einem 4 meter langen Stromkabel mit einer Mikro-Ausgangsbuchse vervollständigt.

Hauptspezifikationen

Anzahl an Köpfen	1	Nettolumen (lm)	1242
Leuchtenkategorie	LED	Halterungen	Decke
Leistung (W)	41W	Umgebung	Innenbeleuchtung
CCT (K)	2700K		
CRI	90		

Optisch

Beleuchtungstyp	Direkt
LED-Typ	Top LED
Light distribution	Symmetrisch
Strahlungswinkel (°)	65
Beam angle C90-270 (°)	65



Beam Angle: 65°

h(m)	E(lx)	D(m)
1	1239	1.27
2	310	2.53
3	138	3.80
4	77	5.07
5	50	6.34

Luminous flux luminaire
1242 lm

Elektrisch

Dimmbar	Yes
Treiber	remote
Notfall	Ausgeschlossen
Isolationsklasse	Ohne
	III

Physikalisch

Farbe	Schwarz
Ausrichtung	fest
Lichtfleckdurchmesser (mm)	400

Suspension Cone Ø 400



LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac
60.8919



LED power supply source for remote installation, 48V/120W. 220/240 Vac
60.9170



DALI 12-48V Dimmer
60.9678



LED Power Supply Source for remote installation. 48V. 100Vac (150W)-240Vac (200W)
60.9607



Casambi Controller 220-240V. Remote Installation
60.9392



0/1-10V & Push 12-48V Dimmer
60.9395