

Suspension Cone Ø 400

Neues Produkt

03.8443.14 - Schwarz

Pendelleuchte mit integriertem Befestigungssystem für die Installation in Infra-Structure Episode 2. Jedes Leuchtelement wird mit einem 4 meter langen Stromkabel mit einer Mikro-Ausgangsbuchse vervollständigt.


Pendelleuchte mit integriertem Befestigungssystem für die Installation in Infra-Structure Episode 2. Jedes Leuchtelement wird mit einem 4 meter langen Stromkabel mit einer Mikro-Ausgangsbuchse vervollständigt.

Hauptspezifikationen

Anzahl an Köpfen	1	Nettolumen (lm)	1982
Leuchtenkategorie	LED	Halterungen	Decke
Leistung (W)	41W	Umgebung	Innenbeleuchtung
CCT (K)	3000K		
CRI	90		

Optisch

Beleuchtungstyp	Direkt
LED-Typ	Top LED
Light distribution	Symmetrisch
Strahlungswinkel (°)	65
Beam angle C90-270 (°)	65



Luminous flux luminaire
1982 lm

Elektrisch

Dimmbar	Yes
Treiber	remote Ausgeschlossen
Notfall	Ohne
Isolationsklasse	III

Physikalisch

Farbe	Schwarz
Ausrichtung	fest
Lichtfleckdurchmesser (mm)	400

Suspension Cone Ø 400



LED power supply source for remote installation, 48V/120W. 220/240 Vac
60.9170



Casambi Controller 220-240V. Remote Installation
60.9392



LED Power Supply Source for remote installation. 48V. 100Vac (150W)-240Vac (200W)
60.9607



LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac
60.8919



0/1-10V & Push 12-48V Dimmer
60.9395



DALI 12-48V Dimmer
60.9678