

The Tracking Magnet Surface Profile Inner Mechanical Corner

■ 06.5016.05 - Hochglänzendes Aluminium

Elektromechanische Profile für Aufputzmontage oder zum Aufhängen mit einer Länge von 1 m bis 3 m.



Hauptspezifikationen

Halterungen	Oberfläche
Umgebung	Innenbeleuchtung

Elektrisch


Spannung (V)	48
Notfall	Ohne

Physikalisch

Farbe	Hochglänzendes Aluminium
Gewicht (kg)	0.2
Länge (mm)	55

Note

Innenwinkel. Nur für die Surface-Ausführung.



GWT
850°

The Tracking Magnet Surface Profile Inner Mechanical Corner



The Tracking Magnet Profile
Intermediate Connector
Flexible/Electrical Corner
08.0614.14



Ceiling fixing kit
08.0615.00



Suspension rod with 1m rose. M6
thread
60.3014.14



Suspension rod with 1m rose. M6
thread
60.3014.11



4m suspension steel cable
08.8634.00



1 m suspension rod with ceiling rose
with m6 thread
60.3097.11



4-pole, 0.75 mm² section, 4-meter long,
transparent power cable
06.0157.00



1 m suspension rod with ceiling rose
with m6 thread
60.3097.14



Recessed power supply rose
08.8889.14



Recessed power supply rose
08.8889.40



The Tracking Magnet
Surface/Suspension Profile End Caps
06.5017.05



Surface rose
08.8883.14A



Ceiling fixing kit
08.0616.00



Surface rose
08.8883.40A