

## The Tracking Magnet Surface Profile Inner Mechanical Corner

■ 06.5016.14 - Schwarz

Elektromechanische Profile für Aufputzmontage oder zum Aufhängen mit einer Länge von 1 m bis 3 m.



### Hauptspezifikationen

|             |                  |
|-------------|------------------|
| Halterungen | Oberfläche       |
| Umgebung    | Innenbeleuchtung |

### Elektrisch


|              |      |
|--------------|------|
| Spannung (V) | 48   |
| Notfall      | Ohne |

### Physikalisch

|              |         |
|--------------|---------|
| Farbe        | Schwarz |
| Gewicht (kg) | 0.2     |
| Länge (mm)   | 55      |

### Note

Innenwinkel. Nur für die Surface-Ausführung.



GWT  
850°

## The Tracking Magnet Surface Profile Inner Mechanical Corner



The Tracking Magnet Profile  
Intermediate Connector  
Flexible/Electrical Corner  
08.0614.14



Recessed power supply rose  
08.8889.40



4m suspension steel cable  
08.8634.00



Ceiling fixing kit  
08.0615.00



1 m suspension rod with ceiling rose  
with m6 thread  
60.3097.14




Suspension rod with 1m rose. M6  
thread  
60.3014.11



The Tracking Magnet  
Surface/Suspension Profile End Caps  
06.5017.14



Suspension rod with 1m rose. M6  
thread  
60.3014.14



Surface rose  
08.8883.14A




---

4-pole, 0.75 mm² section, 4-meter long,  
transparent power cable  
06.0157.00




---

Recessed power supply rose  
08.8889.14




---

Surface rose  
08.8883.40A




---

1 m suspension rod with ceiling rose  
with m6 thread  
60.3097.11




---

Ceiling fixing kit  
08.0616.00