

Alfia Sandblasted Glass

822801.3 - Anthracite

Square luminaire for installation in the wall – recessed.

Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). Glass diffuser: transparent or sandblasted, fixed to the frame through a robotic gluing system.

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP54

In compliance with EN 60598-1 standards

Class of insulation: mains: I, LED module: II, III

Installation: MiniAlfia is equipped with two cable holders for three single wires. Alfia is equipped with two cable holders for 5<ø<10mm cables. Outdoor use requires suitable flexible cables assuring the watertightness of the cable holders. Installation requires a dedicated box to be ordered separately.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

Main specifications

Power (W) System power (W) CCT (K) CRI Net lumen (Im)	4 8.8 3000K 80 401	Mountings Environment	Wall recessed Outdoor
Optical Lighting type	Direct		Lux H = 0.8 m
LED type Light distribution Optical type	Power LED Asymmetric Wide flood	90° 60° cd/1000 lm - c0/C180 C90/C270	$ \begin{array}{c} $

Electrical Frequency (Hz) Voltage (V)

Dimmable Driver type Emergency

Insulation class

L

Physical

Color

Anthracite

50-60


No

220-240

Without

Not dimmable

Alfia Sandblasted Glass



Box for Installation Alfia 60

SPD (Surge Protection Device) 237