







#### 533001.12 - Forest Green

Outdoor / Indoor round luminaire for installation on ceiling or wall – surface mounted.

Configuration: op al plastic diffuser with satin finish for a high light emission uniformity ratio. Die-cast aluminium fixing back-plate and turned aluminium structure and heat sink. Magnetic finish frame to hide the fixing screws.

The luminaire is coated with polyester powders in single or double colour.

Protection rating: IP66

In compliance with EN 60598-1 standards

Class of Insulation: I

Installation: the luminaire is equipped with two IP65 cable holders for rubber cables  $5 < \emptyset < 10$ mm (Anna  $\emptyset 210$  and Ø310) or cables 6<Ø<13mm (Anna Ø410) and a quick-connect 2-pole terminal block. Outdoor installation requires suitable flexible cables assuring the watertightness of the cable holder.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

812



### Main specifications


Power (W)	8.8	Mountings	Ceiling surface, Wall surface
System power (W)	11	Environment	Outdoor
CCT (K)	4000K		
CRI	80		

#### Optical

Net lumen (lm)

Direct
Power LED
Symmetric
Diffused light







Ø 210





**Emergency Physical** 

**Electrical** Frequency (Hz)

Voltage (V)

Driver type

Dimmable

50-60 220-240 Nο

Not dimmable Without

## Insulation class

Color

Forest Green

# Anna 210



SPD (Surge Protection Device) 237