

## Anna 410 Bicolour White/Brown

533029 - White-Brown

Outdoor / Indoor round luminaire for installation on ceiling or wall – surface mounted.

Configuration: opal plastic diffuser with satin finish for a high light emission uniformity ratio. Die-cast aluminium fixing back-plate and turned aluminium structure and heat sink. Magnetic finish frame to hide the fixing screws.

The luminaire is coated with polyester powders in single or double colour.

Protection rating: IP66

In compliance with EN 60598-1 standards

Class of Insulation: I

Installation: the luminaire is equipped with two IP65 cable holders for rubber cables  $5 < \emptyset < 10$ mm (Anna  $\emptyset 210$  and  $\emptyset 310$ ) or cables  $6 < \emptyset < 13$ mm (Anna  $\emptyset 410$ ) and a quick-connect 2-pole terminal block. Outdoor installation requires suitable flexible cables assuring the watertightness of the cable holder.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

2521

## Main specifications


Power (W)	27.9	Mountings	Ceiling surface, Wall surface
System power (W)	34	Environment	Outdoor
CCT (K)	3000K		
CRI	80		

### Optical

Net lumen (lm)

Direct
Power LED
Symmetric
Diffused ligh





# Electrical

Frequency (Hz)	50-60	Insulation class
Voltage (V)	220-240	
Dimmable	No	
Driver type	Not dimmable	

Without

# Emergency Physical

Color White-Brown

# Anna 410 Bicolour White/Brown



SPD (Surge Protection Device) 237