





## Anna 410 Bicolour White/Green Dimmable Dali

533026-300 - White-Green

Outdoor / Indoor round luminaire for installation on ceiling or wall – surface mounted.

Configuration: opal plastic diffuser with satin finish for a high light emission uniformity ratio. Die-cast aluminium fixing back-plate and turned aluminium structure and heat sink. Magnetic finish frame to hide the fixing screws. The luminaire is coated with polyester powders in single or double colour.

Protection rating: IP66

In compliance with EN 60598-1 standards

Class of Insulation: I

Installation: the luminaire is equipped with two IP65 cable holders for rubber cables 5<@<10mm (Anna @210 and @310) or cables 6<@<13mm (Anna @410) and a quick-connect 2-pole terminal block. Outdoor installation requires suitable flexible cables assuring the watertightness of the cable holder.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

Main specifications Power (W) System power (W) CCT (K) CRI Net lumen (Im)	27.9 34 4000K 80 2712	Mountings Environment	Ceiling surface, Wall surface Outdoor
Optical			
Lighting type LED type Light distribution Optical type	Direct Power LED Symmetric Diffused light	90* 60° 280 30° ed/1000 lm - C0/C180 ···· C90/C270	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
Electrical			
Frequency (Hz) Voltage (V) Dimmable Driver type Emergency	50-60 220-240 Yes Electronic dimmable DALI Without	Insulation class	I
Physical			
Color	White-Green		

## Anna 410 Bicolour White/Green Dimmable Dali



SPD (Surge Protection Device) 237