

Anna 410 Bicolour White/Yellow

533061 - White-Yellow

Outdoor / Indoor round luminaire for installation on ceiling or wall – surface mounted.

Configuration: opal plastic diffuser with satin finish for a high light emission uniformity ratio. Die-cast aluminium fixing back-plate and turned aluminium structure and heat sink. Magnetic finish frame to hide the fixing screws.

The luminaire is coated with polyester powders in single or double colour.

Protection rating: IP66

In compliance with EN 60598-1 standards

Class of Insulation: I

Installation: the luminaire is equipped with two IP65 cable holders for rubber cables $5 < \emptyset < 10$ mm (Anna $\emptyset 210$ and $\emptyset 310$) or cables $6 < \emptyset < 13$ mm (Anna $\emptyset 410$) and a quick-connect 2-pole terminal block. Outdoor installation requires suitable flexible cables assuring the watertightness of the cable holder.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

Main specifications


Power (W)	27.9	Mountings
System power (W)	34	Environment
CCT (K)	2700K	
CRI	80	
Net lumen (lm)	2345	

Optical

Direct
Power LED
Symmetric
Diffused ligh



Insulation class



Ceiling surface, Wall surface

Outdoor

Electrical

Frequency (Hz)	50-60
Voltage (V) Dimmable	220-240 No
Driver type	Not dimmable
Emergency	Without

Physical

Color White-Yellow

Anna 410 Bicolour White/Yellow



SPD (Surge Protection Device) 237