



Anna 410 Bicolour White/Yellow Dimmable Dali

533027-300 - White-Yellow

Outdoor / Indoor round luminaire for installation on ceiling or wall – surface mounted.

Configuration: opal plastic diffuser with satin finish for a high light emission uniformity ratio. Die-cast aluminium fixing back-plate and turned aluminium structure and heat sink. Magnetic finish frame to hide the fixing screws.

The luminaire is coated with polyester powders in single or double colour.

Protection rating: IP66

In compliance with EN 60598-1 standards

Class of Insulation: I

Installation: the luminaire is equipped with two IP65 cable holders for rubber cables $5<\emptyset<10$ mm (Anna \emptyset 210 and \emptyset 310) or cables $6<\emptyset<13$ mm (Anna \emptyset 410) and a quick-connect 2-pole terminal block. Outdoor installation requires suitable flexible cables assuring the watertightness of the cable holder.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Mountings

Environment

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.


Main specifications

Power (W)	27.9
System power (W)	34
CCT (K)	3000K
CRI	80
Net lumen (lm)	2712

Optical

Direct
Power LED
Symmetric
Diffused ligh





Ceiling surface, Wall surface

Outdoor wet location

Electrical

Frequency (Hz)	50-60	Insulation class
Voltage (V)	220-240	
Dimmable	Yes	


Driver type Dimmable DALI

Emergency Without

Physical

Color White-Yellow

Anna 410 Bicolour White/Yellow Dimmable Dali



SPD (Surge Protection Device) 237