





Anna 410 Dimmable 1-10V

533021-310.6 - Grey

Outdoor / Indoor round luminaire for installation on ceiling or wall – surface mounted.

Configuration: opal plastic diffuser with satin finish for a high light emission uniformity ratio. Die-cast aluminium fixing back-plate and turned aluminium structure and heat sink. Magnetic finish frame to hide the fixing screws. The luminaire is coated with polyester powders in single or double colour.

Protection rating: IP66

In compliance with EN 60598-1 standards

Class of Insulation: I

Installation: the luminaire is equipped with two IP65 cable holders for rubber cables 5<0<10 mm (Anna 0210 and 0310) or cables 6<0<13 mm (Anna 0410) and a quick-connect 2-pole terminal block. Outdoor installation requires suitable flexible cables assuring the watertightness of the cable holder.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion. Chemical substances affect the anticorrosion covering protection.

Main specifications Power (W) 27.9 Mountings Ceiling surface, Wall surface System power (W) 34 Environment Outdoor CCT (K) 4000K CRI 80 Net lumen (lm) 2712 Optical Lighting type Direct àn lux Max lux Med 172 43 19 11 7 LED type Power LED Light distribution 1.00 778 195 Symmetric 2.00 3.00 4.00 5.00 Optical type Diffused light 86 49 30 α = 60°+ 60° $\beta = 60^{\circ} + 60^{\circ}$ - C0 / C180 ···· C90 / C270 Electrical Frequency (Hz) 50-60 Insulation class I 220-240 Voltage (V) Dimmable Yes Driver type Electronic dimmable 1-10V Without Emergency Physical Color Grey

Anna 410 Dimmable 1-10V



SPD (Surge Protection Device) 237