

## Arcadia L 1240 Long Bracket Dimmable 1-10V

545090-310.4 - Black

Linear luminaire for installation on wall or ceiling - surface mounted.

Configuration: die-cast aluminium closing ends, EN AB-47100 alloy (low copper content), extruded aluminium structure and zinc-coated steel fixing brackets. Glass diffuser: transparent or sandblasted with silkscreen border, fixed to the aluminium through a robotic gluing system.

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP65

In compliance with EN60598-1 standards

Class of insulation: I; RGB: I

Installation: the luminaire is equipped with a piece of cable (approx. 500mm) and an M16 cable-gland (4,5mm<ø<10mm cables) closed with a removable cap. The electrical components are installed on a removable frame accessible by unscrewing the closing ends. Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder.

We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.


### Main specifications


Power (W)	26.4
System power (W)	32
CCT (K)	2700K
CRI	80
Net lumen (lm)	2444

Mountings Ceiling and wall surface Environment Outdoor

#### Optical

Direct
Power LED
Symmetric
Spot





#### Electrical

Frequency (Hz)	50-60
Voltage (V)	220-240
Dimmable	Yes
Driver type	Electronic
	dimmable 1-10V
Emergency	Without

Insulation class

#### **Physical**

Color Black

# Arcadia L 1240 Long Bracket Dimmable 1-10V







3/4 Way Terminal Block 4 Poles Ip68 H2O Stop 215

2 Way Terminal Block 4 Poles Ip68 H2O SPD (Surge Protection Device) Stop 236