


## Arcadia L 940 Short Bracket RGB

■ 545104.4 - Black



Linear luminaire for installation on wall or ceiling – surface mounted.

Configuration: die-cast aluminium closing ends, EN AB-47100 alloy (low copper content), extruded aluminium structure and zinc-coated steel fixing brackets. Glass diffuser: transparent or sandblasted with silkscreen border, fixed to the aluminium through a robotic gluing system.

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

Protection rating: IP65

In compliance with EN60598-1 standards

Class of insulation: I; RGB: I

Installation: the luminaire is equipped with a piece of cable (approx. 500mm) and an M16 cable-gland (4,5mm<ø<10mm cables) closed with a removable cap. The electrical components are installed on a removable frame accessible by unscrewing the closing ends. Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder.

We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

### Main specifications

<b>Power (W)</b>	30.6
<b>System power (W)</b>	38
<b>Mountings</b>	Ceiling and wall surface
<b>Environment</b>	Outdoor

### Optical

<b>Lighting type</b>	Direct
<b>LED type</b>	Power LED
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light

### Electrical

<b>Frequency (Hz)</b>	50-60	<b>Insulation class</b>	I
<b>Voltage (V)</b>	230		
<b>Dimmable</b>	Yes		
<b>Driver type</b>	Dmx		
<b>Emergency</b>	Without		

### Physical

<b>Color</b>	Black
--------------	-------

## Arcadia L 940 Short Bracket RGB



---

Dmx Controller Dimmer Switch For  
Recessed Box  
142




---

Dmx Controller Stand-Alone/Pc  
Interface  
143



---

Dmx Cable Shielded Twisted Pair  
186



---

DMX splitter 512 – electronic device to  
regenerate the monodirectional DMX  
signal 1 Input and 7 output, 12-  
24Vdc\_IP20. Power supply not included  
187