







Belvedere Clove 1 Dimmable 1-10V Anthracite

F001A41B033 - Anthracite

Family of outdoor products consisting of luminaires with a pole of two different heights and suitable for floor installations (ground or buried) and with integrated power supply box.

220-240V power supply included. Ready for installation on solid surface. Box for ground installation to be ordered separately.

Included 2 way terminal block 4 poles IP68 H2O Stop.

Version 110V upon request.

N 4 · • • • • •

Main specifications	LED	Mountings	Ground
Power (W) CCT (K) CRI Net lumen (Im)	8.40 4000K 80 703	Environment	Outdoor wet location
Optical			
Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°)	Direct Power LED Symmetric Diffused light 100 100	90° 90° 60° 60° 30° 315 cd 30° Luminous flux luminaire 703 lm	
Electrical			
Frequency (Hz) Voltage (V) Dimmable Driver Driver type	50-60 220-240 Yes Integrated Dimmable 1-10V	Emergency Insulation class	Without II
Physical			
Color Orientation Weight (kg)	Anthracite Fixed 1.70		
Note			

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection. For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

• over voltage coming from the mains' network where fixture is connected.

• electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.

Belvedere Clove 1 Dimmable 1-10V Anthracite



S.P.D. (SURGE PROTECTION DEVICE) F990E00A000 Box for ground installation F001Z020000