







Belvedere Clove 2 Dimmable 1-10V Deep Brown

F001B21B018 - Deep Brown

Family of outdoor products consisting of luminaires with a pole of two different heights and suitable for floor installations (ground or buried) and with integrated power supply box.

220-240V power supply included. Ready for installation on solid surface. Box for ground installation to be ordered separately.

Included 2 way terminal block 4 poles IP68 H2O Stop.

Version 110V upon request.

N 4 · • • • • •

Main specifications			
Lamp category Power (W) CCT (K) CRI Net lumen (Im)	LED 8.40 2700K 80 631	Mountings Environment	Ground Outdoor wet location
Optical			
Lighting type LED type Light distribution Optical type Beam angle (°) Beam angle C90-270 (°)	Direct Power LED Symmetric Diffused light 100 100	90° 90° 60° 60° 30° 283 cd 30° Luminous flux luminaire 631 lm	
Electrical			
Frequency (Hz) Voltage (V) Dimmable Driver Driver type	50-60 220-240 Yes Integrated Dimmable 1-10V	Emergency Insulation class	Without II
Physical			
Color Orientation Weight (kg)	Deep Brown Fixed 2.10		
Note			

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection. For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

• over voltage coming from the mains' network where fixture is connected.

• electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.

Belvedere Clove 2 Dimmable 1-10V Deep Brown



Box for ground installation F001Z020000

S.P.D. (SURGE PROTECTION DEVICE) F990E00A000