









Belvedere Clove 2 Non Dimmable Forest Green

F001B31A012 - Forest Green

Family of outdoor products consisting of luminaires with a pole of two different heights and suitable for floor installations (ground or buried) and with integrated power supply box.

220-240V power supply included. Ready for installation on solid surface. Box for ground installation to be ordered separately.

Included 2 way terminal block 4 poles IP68 H2O Stop.


Version 110V upon request.

N 4 - 1				
Main	spe	CITIC	catic	ns

Lamp category	LED	Mountings	Ground
Power (W)	8.40	Environment	Outdoor wet location
CCT (K)	3000K		
CRI	80		
Net lumen (lm)	657		

Optical

Lighting type Direct
LED type Power LED
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 100
Beam angle C90-270 (°) 100



Luminous flux luminaire 657 lm

Electrical

Frequency (Hz) 50-60 Insulation class II
Dimmable No
Driver Integrated
Driver type Non Dimmable
Emergency Without

Emergency Physical

 Color
 Forest Green

 Orientation
 Fixed

 Weight (kg)
 2.10

Note

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.


For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- \bullet electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.

Belvedere Clove 2 Non Dimmable Forest Green



S.P.D. (SURGE PROTECTION DEVICE) F990E00A000

Box for ground installation F001Z020000