

*Concrete, crema d'orcia basaltina H = 48 mm



Camouflage 240 mm Non Dimmable Crema d'Orcia Stone

F1317090 - Crema d'Orcia Stone

Collection of products for outdoor use, for wall instal-lation with LED light source

Dissipating aluminum body with diffuser in transpar-ent polycarbonate.

944

The Crema d'Orcia and Basaltina stone finishes are made by fastening high-strength, high-resistance ad-hesive to a stone plate created by means of mechani-cal machining from a solid block.

The concrete finishing is made by fastening a poured cement plate reinforced with fiberglass using a single component high strength, high-resistance adhesive. The Primer version is painted after installation with normal water-based colors (tempera, stucco, water-based paints) to ensure maximum uniformity with the architecture.

The aluminum versions are finished with a high-re-sistance coating: after a sandblasting treatment of all components to make the surface porous and ensure a greater adhesion of the paint, the external coating is applied with a double layer with epoxy powders according to the QUALICOAT standard. The first layer of epoxy powder gives chemical and mechani-cal resistance, the second finishing layer of polyester powder ensures resistance to UV rays and atmos-pheric agents.

The painted surfaces are treated with alkaline and acidic washes, then rinsed with demineralized water, subjected to a chemical conversion treatment to protect against oxidation.

Integrated 220/240V power supply. Supplied with a 1000 mm lenght outgoing neoprene cable. Version 110V upon request.


Main specifications

Lamp category	LED	Mountings	Wall surface
Power (W)	12	Environment	Outdoor wet location
CCT (K)	4000K		
CRI	80		

Optical

Net lumen (lm)

Lighting type Direct
LED type Power LED
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 151
Beam angle C90-270 (°) 151



Electrical

Frequency (Hz)	50-60	Emergency	Without
Voltage (V)	220-240	Insulation class	1
Dimmable	No		
Driver	Integrated		
Driver type	Non Dimmable		

Physical

•		
Color	Crema d'Orcia	
	Stone	
Orientation	Fixed	
Weight (kg)	1.50	

Note

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the coating.

For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- \bullet electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.

Camouflage 240 mm Non Dimmable Crema d'Orcia Stone



S.P.D. (SURGE PROTECTION DEVICE) F990E00A000