





F011W30B030 - Black

Luminaire for wall-mounting with diffuse light emission and fixed head.

Rose, frame and cone in 316L polished or painted stainless steel or polished brass finishes. Structural parts have  $been \ treated \ with \ a \ chemical \ conversion \ process \ for \ effective \ resistance \ against \ atmospheric \ conditions. \ Diffuser$ in photo-recorded and injection molded UV-resistant opalescent polycarbonate. LED light source included. Integrated 220-240V 1-10V dimmable electrical power.

Connection is quickly ensured in the rose with the plug & play electrical connection and the IP68 connector included. Clamp bracket included.

110V version upon request

## Main specifications


Number of heads	1
amp category	LED
Power (W)	11
CCT (K)	3000K
CRI	80

Net lumen (lm) 658 Mountings

Ceiling and wall surface

# Optical


Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Diffused light
Beam angle (°)	112
Beam angle C90-270 (°)	112



Luminous flux luminaire

Without

Beam Angle:		112°
h(m)	E(lx)	D(m)
1	233	2.95
2	58	5.91
3	26	8.86
4	15	11.81
5	9	14.76





### **Electrical**

Frequency (Hz)	50-60	Emergency
Voltage (V)	220-240	Insulation class
Dimmable	Yes	
Driver	Integrated	
Driver type	Dimmable 1-10V	

# **Physical**

Color	Black
Orientation	Fixed
Weight (kg)	2.1
Spot diameter (mm)	208
Length (mm)	336

## Note

110V version upon request.