






F011W40B030 - Black

Luminaire for wall-mounting with diffuse light emission and fixed head.

Rose, frame and cone in 316L polished or painted stainless steel or polished brass finishes. Structural parts have been treated with a chemical conversion process for effective resistance against atmospheric conditions. Diffuser in photo-recorded and injection molded UV-resistant opalescent polycarbonate. LED light source included. Integrated 220-240V 1-10V dimmable electrical power.

Connection is quickly ensured in the rose with the plug & play electrical connection and the IP68 connector included. Clamp bracket included.

110V version upon request



 Number of heads
 1

 Lamp category
 LED

 Power (W)
 11

 CCT (K)
 4000K

 CRI
 80

Net lumen (lm) Mountings 703


Without

Ceiling and wall surface




## Optical

Lighting type Direct
LED type LED array
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 112
Beam angle C90-270 (°) 112



Luminous flux luminaire 703 lm

Beam Angle:		112°
h(m)	E(lx)	D(m
1	249	2.95
2	62	5.91
3	28	8.86
4	16	11.81
5	10	1/1 7/





## Electrical

Frequency (Hz) 50-60 Emergency
Voltage (V) 220-240 Insulation class
Dimmable Yes
Driver Integrated
Driver type Dimmable 1-10V

## Physical

 Color
 Black

 Orientation
 Fixed

 Weight (kg)
 2.1

 Spot diameter (mm)
 208

 Length (mm)
 336

## Note

110V version upon request.