





F011W20D030 - Black

Luminaire for wall-mounting with diffuse light emission and fixed head.

Rose, frame and cone in 316L polished or painted stainless steel or polished brass finishes. Structural parts have been treated with a chemical conversion process for effective resistance against atmospheric conditions. Diffuser in photo-recorded and injection molded UV-resistant opalescent polycarbonate. LED light source included. Integrated 220-240V DALI dimmable electrical power.

Connection is quickly ensured in the rose with the plug & play electrical connection and the IP68 connector included. Clamp bracket included.

110V version upon request

## Main specifications

 Number of heads
 1

 Lamp category
 LED

 Power (W)
 11

 CCT (K)
 2700K


 CRI
 80

Net lumen (lm) Mountings 613

Ceiling and wall surface




Lighting type Direct
LED type LED array
Light distribution Symmetric
Optical type Diffused light
Beam angle (°) 112
Beam angle C90-270 (°) 112



Luminous flux luminaire

Beam Angle:		112°
h(m)	E(lx)	D(m
1	217	2.95
2	54	5.91
3	24	8.86
4	14	11.81
5	9	14 74





## **Electrical**

Frequency (Hz) 50-60 Emergency Without Voltage (V) 220-240 Insulation class I Dimmable Yes Integrated

Dimmable DALI

## Physical

Driver type

 Color
 Black

 Orientation
 Fixed

 Weight (kg)
 2.1

 Spot diameter (mm)
 208

 Length (mm)
 336

## Note

110V version upon request.