


### Cassiopea Round Dimmable Dali

7511413-300.0 - Inox



Square or round luminaire – for installation in-ground where recessing depth are limited (up to 120mm) – recessed.

Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). AISI 316L stainless steel outer frame. Glass diffuser: transparent with silkscreen border.

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

Protection rating: IP67

In compliance with EN 60598-1 standards

Class of insulation: I

Installation: the luminaire is equipped with a piece of cable with a 2-way connector for 3-conductor cables (H2O STOP) for an easy-to-make connection. RGB version: the luminaire is equipped with 2 pieces of cable, no H2O STOP connector provided. Outdoor use requires suitable flexible cables. Installation requires a dedicated box to be ordered separately. It is important to provide a >300mm gravel layer or a drain system (for concrete surfaces) to ensure good drainage and to avoid water stagnation.

We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.


Chemical substances affect the anticorrosion covering protection.

#### Main specifications

Power (W)	22	Mountings	Floor recessed
System power (W)	28	Environment	Outdoor
CCT (K)	2700K		
CRI	80		
Net lumen (lm)	1783		

#### Optical

Lighting type	Direct
LED type	Power LED
Light distribution	Symmetric
Optical type	Medium



m	α	β	lux Max	lux Med
5.00			287	173
4.00			449	270
3.00			798	479
2.00			1795	1079
1.00			7181	4314

#### Electrical

Frequency (Hz)	50-60	Insulation class	I
Voltage (V)	110-240		
Dimmable	Yes		
Driver type	Electronic dimmable DALI		
Emergency	Without		

#### Physical

Color	Inox
-------	------

# Cassiopea Round Dimmable Dali



Box for Installation Cassiopea Round  
73



3/4 Way Terminal Block 4 Poles Ip68  
H2O Stop  
215



SPD (Surge Protection Device)  
237