

## Cassiopea Square Dimmable Dali

7611513-300.0 - Inox



Square or round luminaire – for installation in-ground where recessing depth are limited (up to 120mm) – recessed.

Configuration: die-cast aluminium structure, EN AB-47100 alloy (low copper content). AISI 316L stainless steel outer frame. Glass diffuser: transparent with silkscreen border.

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Areas affected by alkaline and acid washing to clean the surfaces completely, then rinsed with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting.

Protection rating: IP67

In compliance with EN 60598-1 standards

Class of insulation: I

Installation: the luminaire is equipped with a piece of cable with a 2-way connector for 3-conductor cables (H2O STOP) for an easy-to-make connection. RGB version: the luminaire is equipped with 2 pieces of cable, no H2O STOP connector provided. Outdoor use requires suitable flexible cables. Installation requires a dedicated box to be ordered separately. It is important to provide a >300mm gravel layer or a drain system (for concrete surfaces) to ensure good drainage and to avoid water stagnation.

We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.


Chemical substances affect the anticorrosion covering protection.

### Main specifications

|                         |       |                    |                |
|-------------------------|-------|--------------------|----------------|
| <b>Power (W)</b>        | 22    | <b>Mountings</b>   | Floor recessed |
| <b>System power (W)</b> | 28    | <b>Environment</b> | Outdoor        |
| <b>CCT (K)</b>          | 2700K |                    |                |
| <b>CRI</b>              | 80    |                    |                |
| <b>Net lumen (lm)</b>   | 1783  |                    |                |


### Optical

|                           |           |
|---------------------------|-----------|
| <b>Lighting type</b>      | Direct    |
| <b>LED type</b>           | Power LED |
| <b>Light distribution</b> | Symmetric |
| <b>Optical type</b>       | Medium    |



| m    | α | β | lux Max | lux Med |
|------|---|---|---------|---------|
| 5.00 |   |   | 287     | 173     |
| 4.00 |   |   | 449     | 270     |
| 3.00 |   |   | 798     | 479     |
| 2.00 |   |   | 1795    | 1079    |
| 1.00 |   |   | 7181    | 4314    |

α = 15.0° ± 15.0°      β = 15.0° ± 15.0°



### Electrical

|                       |                          |                         |   |
|-----------------------|--------------------------|-------------------------|---|
| <b>Frequency (Hz)</b> | 50-60                    | <b>Insulation class</b> | I |
| <b>Voltage (V)</b>    | 110-240                  |                         |   |
| <b>Dimmable</b>       | Yes                      |                         |   |
| <b>Driver type</b>    | Electronic dimmable DALI |                         |   |
| <b>Emergency</b>      | Without                  |                         |   |

### Physical

|              |      |
|--------------|------|
| <b>Color</b> | Inox |
|--------------|------|

## Cassiopea Square Dimmable Dali




---

Box for Installation Cassiopea Square  
74



---

3/4 Way Terminal Block 4 Poles Ip68  
H2O Stop  
215



---

SPD (Surge Protection Device)  
237