

**Clessidra 20°+20°**

■ F1583006 - Grey

Diffused direct/indirect-light wall lighting device. Body obtained by means of aluminium pressofusion and diffusers in PMMA. Aluminium wall attachment with cover in PA66. Available in white-painted or chrome-plated for indoor version and dark brown-painted or dark gray-painted for outdoor version. High-efficiency lenses specially designed for the application, non-replaceable. Wide range (100-240Volt) power pack integrated in the body. Level IP55

**Main specifications**

<b>Number of heads</b>	2	<b>Environment</b>	Indoor Outdoor wet location
<b>Power (W)</b>	10		
<b>CCT (K)</b>	3000K		
<b>Net lumen (lm)</b>	637		
<b>Mountings</b>	Wall		

**Optical**

<b>Lighting type</b>	Indirect, Direct
<b>LED type</b>	LED array
<b>Light distribution</b>	Symmetric
<b>Optical type</b>	Diffused light

**Electrical**

<b>Frequency (Hz)</b>	50/60	<b>Emergency</b>	Without
<b>Voltage (V)</b>	100-240	<b>Insulation class</b>	I
<b>Lamp holder</b>	COB LED		
<b>Driver</b>	Integrated		
<b>Driver type</b>	Non Dimmable		

**Physical**

<b>Color</b>	Grey
<b>Weight (kg)</b>	1.1

