

Emma 110 Cob Led Unidirectional

117279146.A.1 - White

Luminaire for installation on wall – surface mounted.

Configuration: die-cast aluminium fixing base and frames, EN AB-47100 alloy (low copper content), extruded aluminium body. Glass diffuser: transparent.

Double layer coating for high resistance to corrosion: the aluminium components are painted with a double coat using powders that are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components that have been sandblasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. Protection rating: IP66

In compliance with EN 60598-1 standards

Class of insulation: I

Installation: wiring through two cable holders ($8mm < \emptyset < 12mm$ cables). Outdoor use requires suitable flexible cables assuring the watertightness of the cable holder. A quick clamp placed in the wiring unit allows an easy connection and disconnection for installation or maintenance.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Environment

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

Main specifications


Power (W)	12
System power (W)	14.5
CCT (K)	2700K
CRI	80
Net lumen (lm)	1569

Mountings

system power (w)	14.5
CCT (K)	2700k
CRI	80
Net lumen (lm)	1569

Optical

Lighting type	Direct
LED type	LED array
Light distribution	Symmetric
Optical type	Medium



Wall surface

 $\beta = 10.0^{\circ} + 10.0^{\circ}$

Outdoor


Electrical

Frequency (Hz)	50-60	Insulation class
Voltage (V)	110-240	
Dimmable	No	
Driver type	Not dimmable	
Emergency	Without	

Physical

Color White

Emma 110 Cob Led Unidirectional



SPD (Surge Protection Device) 237