

IC Ceiling Wall 1 Outdoor Black

■ F012H00C030 - Black




Wall- or ceiling-mounted light fitting with diffuse light for exterior use available in two sizes. Frame in brushed stainless steel, brushed brass finish or painted opaque black or burgundy. The structure of the fitting is treated with a chemical conversion process for effective resistance to atmospheric agents. Special attention is recommended during installation and maintenance to prevent damage to the powder coating. Opalescent diffuser in shiny white translucent blown glass. The light comes with seals for IP-rated connection.

Main specifications

Lamp category	LED retrofit
Mountings	Ceiling and wall surface
Environment	Outdoor

Optical


Lighting type	Direct
Light distribution	Symmetric
Optical type	Diffused light



Beam Angle: 0°

h(m)	E(lx)	D(m)
1	57	
2	14	
3	6	
4	4	
5	0	

Luminous flux luminaire
700 lm



Electrical

Frequency (Hz)	50-60
Voltage (V)	220-240
Dimmable	Yes
Emergency	Without
Insulation class	I


Physical

Color	Black
Orientation	Fixed
Weight (kg)	2.2

Note

Bulb not included. LED: max 8W - E14


Certification / Marking



IC Ceiling Wall 1 Outdoor Black



LED 8W E14 800lm 3000K [e] Dimmable
RF26565



LED 8W E14 700lm 2700K [e] Dimmable
RF26767