

IC Ceiling Wall 2 Outdoor Brushed Stainless Steel

New

■ F012J00C005 - Brushed Stainless Steel


Wall- or ceiling-mounted light fitting with diffuse light for exterior use available in two sizes. Frame in brushed stainless steel, brushed brass finish or painted opaque black or burgundy. The structure of the fitting is treated with a chemical conversion process for effective resistance to atmospheric agents. Special attention is recommended during installation and maintenance to prevent damage to the powder coating. Opalescent diffuser in shiny white translucent blown glass. The light comes with seals for IP-rated connection.

Main specifications

Lamp category	LED retrofit
Mountings	Ceiling and wall surface
Environment	Outdoor wet location


Optical

Lighting type	Direct
Light distribution	Symmetric
Optical type	Diffused light



Beam Angle:	0°	
h(m)	E(lx)	D(m)
1	86	
2	21	
3	10	
4	5	
5	0	

Luminous flux luminaire
1400 lm



Electrical

Frequency (Hz)	50-60
Voltage (V)	220-240
Dimmable	Yes
Emergency	Without
Insulation class	I

Physical

Color	Brushed Stainless Steel
Orientation	Fixed
Weight (kg)	3.8

Note

Bulb not included. LED: max 15W - E27

