





Idra 130 Power Led Sandblasted Glass

255628.0 - Inox

Round luminaire for installation in-ground – recessed.

Configuration: AISI 316 deep-drawn stainless steel structure with milled AISI 316L stainless steel finish frame. Glass diffuser: transparent or sandblasted. The stainless steel structure allows installation in extreme conditions (sea or road salt).

Protection rating: IP67

In compliance with EN 60598-1 standards

Class of insulation: mains: I; low voltage: III

Installation: the luminaire is equipped with a piece of cable with a 2-way connector for 3-conductor cables (H2O STOP) for an easy-to-make connection. LED 24V is equipped with a dc/dc highly efficient converter that removes electromagnetic interference and allows parallel wiring and is protected against polarity reversal and sudden voltage peak. Outdoor use requires suitable flexible cables. Installation requires a dedicated box for installation (to be ordered separately). It is important to provide a >400mm gravel layer or a drain system (for concrete surface) to ensure good drainage and to avoid water stagnation.

We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion. Chemical substances affect the anticorrosion covering protection.

Ν

Main specifications			
Power (W) System power (W) CCT (K) CRI Net lumen (Im)	3.3 4.5 3000K 80 130	Mountings Environment	Floor recessed Outdoor
Optical			
Lighting type LED type Light distribution Optical type	Direct Power LED Symmetric Diffused light	600 120° 90° - C0 / C180 - C0 / C180 - C0 / C180 - C0 / C270	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$
Electrical			
Frequency (Hz) Voltage (V) Dimmable Driver type Emergency	50-60 24 No Not dimmable Without	Insulation class	III
Physical			
Color	Inox		

Idra 130 Power Led Sandblasted Glass







Box for Installation Idra 130 85

3/4 Way Terminal Block 4 Poles Ip68 H2O Stop 215

Power Supply 8W 100÷240Vac/24Vdc 350mA lp20 150







Power Supply 100÷240Vac/ 8W at 24Vdc/ 6W at 350mA Ip65 106 Power Supply 10W 110÷240Vac/24Vdc Ip20 87

Power Supply 10W 110÷240Vac/24Vdc Ip67 175



Power Supply 50W 120÷240V/24Vdc Ip67 155 Power Supply 70W 220÷240V/24Vdc Ip67 110