


Idra 130 Transparent Glass

253315.0 - Inox



Round luminaire for installation in-ground – recessed.

Configuration: AISI 316 deep-drawn stainless steel structure with milled AISI 316L stainless steel finish frame.

Glass diffuser: transparent or sandblasted. The stainless steel structure allows installation in extreme conditions (sea or road salt).

Protection rating: IP67

In compliance with EN 60598-1 standards

Class of insulation: mains: I; low voltage: III

Installation: the luminaire is equipped with a piece of cable with a 2-way connector for 3-conductor cables (H2O STOP) for an easy-to-make connection. LED 24V is equipped with a dc/dc highly efficient converter that removes electromagnetic interference and allows parallel wiring and is protected against polarity reversal and sudden voltage peak. Outdoor use requires suitable flexible cables. Installation requires a dedicated box for installation (to be ordered separately). It is important to provide a >400mm gravel layer or a drain system (for concrete surface) to ensure good drainage and to avoid water stagnation.

We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.


Chemical substances affect the anticorrosion covering protection.

Main specifications

Power (W)	12
System power (W)	35
Mountings	Floor recessed
Environment	Outdoor

Optical

Lighting type	Direct
Light distribution	Symmetric
Optical type	Wide flood



m	lux Max	lux Med
5.00	73	48
4.00	114	74
3.00	203	132
2.00	458	297
1.00	1831	1189

Electrical

Frequency (Hz)	50-60
Voltage (V)	12
Lamp holder	GU5.3
Dimmable	No
Driver type	Not dimmable

Emergency	Without
Insulation class	III

Physical

Color	Inox
-------	------

Idra 130 Transparent Glass



Box for Installation Idra 130
85



3/4 Way Terminal Block 4 Poles Ip68
H2O Stop
215



Transformer 50W 230V/12V 50Hz Ip66
16



Transformer 200W 230V/12V 50Hz Ip66
17



Transformer 300W 230V/12V 50Hz Ip66
18