

Idra 220 Power Led Transparent Glass

257728.A.0 - Inox

Round luminaire for installation in-ground – recessed.

Configuration: AISI 316 deep-drawn stainless steel structure with milled AISI 316L stainless steel finish frame. Glass diffuser: transparent or sandblasted. The stainless steel structure allows installation in extreme conditions (sea or road salt).

Protection rating: IP67

In compliance with EN 60598-1 standards

Class of insulation: mains: I; low voltage: III

Installation: the luminaire is equipped with a piece of cable with a 2-way connector for 3-conductor cables (H2O STOP) for an easy-to-make connection. LED 24V is equipped with a dc/dc highly efficient converter that removes electromagnetic interference and allows parallel wiring and is protected against polarity reversal and sudden voltage peak. Outdoor use requires suitable flexible cables. Installation requires a dedicated box for installation (to be ordered separately). It is important to provide a >400mm gravel layer or a drain system (for concrete surface) to ensure good drainage and to avoid water stagnation.

We recommend the use of a connection system with a protection degree greater than or equal to the protection degree of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.


Chemical substances affect the anticorrosion covering protection.

Main specifications

| Power (W) | 15 | Mountings | Floor recessed |
|------------------|-------|-------------|----------------|
| System power (W) | 16 | Environment | Outdoor |
| CCT (K) | 3000K | | |
| CRI | 90 | | |
| Net lumen (lm) | 741 | | |

Optical

| Lighting type | Direct |
|--------------------|-----------|
| LED type | Power LED |
| Light distribution | Symmetric |
| Optical type | Medium |



Electrical

| Frequency (Hz) | 50-60 | Insulation class |
|----------------|--------------|------------------|
| Voltage (V) | 220-240 | |
| Dimmable | No | |
| Driver type | Not dimmable | |

Without


Physical

Emergency

Color Inox

Idra 220 Power Led Transparent Glass







3/4 Way Terminal Block 4 Poles Ip68 H2O Stop 215



SPD (Surge Protection Device) 237